



SIEMENS

Ingenuity for life

Install the "Scan to HIT" app and scan the DMC code on the product to get product information.



Valves and actuators: Acvatix hydronics. Everything under control.

Fast and easy planning, installation and commissioning

[siemens.com/acvatix](https://www.siemens.com/acvatix)

The right solution for every hydronic project

Highlights

- Products for any hydronic requirement
- Support and practical tools for every project phase
- High level of investment protection thanks to long life and maximum reliability
- Easy and quick planning, installation and commissioning

Acvatix™ is a versatile range of valves and actuators for superior ease of use, maximum control accuracy and energy efficiency. It allows you to meet virtually any control and hydronic requirement associated with the generation, distribution and use of heating and cooling. Siemens provides useful tools and extensive knowledge to assist you in every project phase.

Benefit from our decades of experience

You receive the highest quality and maximum reliability because Acvatix valves and actuators are improved continually based on Siemens' many years of experience in the field and rigorous testing in the in-house HVAC laboratory. The result: Acvatix products have been used for decades in millions of successful installations worldwide.

Selection and engineering made easy

The HIT Portal, the valve slide ruler or the Combi Valve Sizer app allow you to quickly find the right products for your application. You can use the HIT Portal to design the entire HVAC application step by step, including specifications complete with plant diagrams and lists of materials.



Installation in a few simple steps

Acvatix products make your daily work easier, whether it is intuitive manual operation irrespective of the installation position or valve actuator coupling with just one screw or via bayonet mount. Lost the instructions for a product? No problem! Simply use the "Scan to HIT" app from Siemens to scan the data matrix code on the product and receive complete product information.

Intelligent comfort for optimized plant operation

Acvatix offers rapid commissioning and efficient plant control. Easy-to-see operating status and position indicators speed up commissioning, testing and maintenance of the plant and help with troubleshooting. State-of-the-art products such as pressure independent combi valves save time and effort through automatic hydronic balancing. Acvatix is synonymous with robust design, outstanding reliability as well as minimal need for maintenance.



The future of construction

Boost your efficiency by using BIM (Building Information Modeling) for planning. The holistic process that is transforming planning, construction and management of buildings and infrastructures accelerates amongst others construction and early error detection.

[siemens.com/bim-data](https://www.siemens.com/bim-data)

The Combi Valve Sizer app makes it easy to select the right Acvatix combi valve and actuator. This makes designing energy-efficient HVAC systems easier than ever.



Our goal is to create perfect places – with the right building automation technologies, tools, and services that will help our customers to better reach their individual goals more quickly and easily. This encompasses short innovation cycles as well as the fulfillment of stricter security requirements and the growing importance of energy efficiency and sustainability.

#CreatingPerfectPlaces

[siemens.com/perfect-places](https://www.siemens.com/perfect-places)



											Recommended media											
		2-port valve	3-port valve	4-port valve	6-port valve	PN class	Type of connection	Silicon-free grease	Closed circuits	Open circuits	Chilled water	Cooling water ¹⁾	Drinking water	Low-temperature hot water	High-temperature hot water	Water glycol mixture	Saturated steam	Superheated steam	Heat transfer oil	Media containing mineral oils	Refrigerants	Refrigerants (ammonia)
Globe valves	VDN../VEN../VUN..	■				10	ET		■		■			■		■						
	VD1..CLC	■				10	ET		■		■			■		■						
	VVP45..	■				16	ET		■		■			■		■						
	VXP45..		■			16	ET		■		■			■		■						
	VMP45..		■			16	ET		■		■			■		■						
	VVP47..	■				16	ET		■		■			■		■						
	VXP47..		■			16	ET		■		■			■		■						
	VMP47..		■			16	ET		■		■			■		■						
	VVG41..	■				16	ET	■	■	■	■	■		■	■	■	■	■				
	VXG41..		■			16	ET	■	■	■	■	■		■	■	■						
	VXG41..01 ⁴⁾		■			16	ET	■	■	■	■	■	■	■	■	■						
	VVG44..	■				16	ET	■	■		■			■		■						
	VXG44..		■			16	ET	■	■		■			■		■						
	VVG549..	■				25	ET		■		■	■		■	■	■						
	VVI46../2	■				16	IT		■		■			■		■						
	VXI46../2		■			16	IT		■		■			■		■						
	VVF22..	■				6	F	■	■		■			■	■	■						
	VXF22..		■			6	F	■	■		■			■	■	■						
	VVF32..	■				10	F	■	■		■			■	■	■						
	VXF32..		■			10	F	■	■		■			■	■	■						
	VVF42..	■				16	F	■	■		■			■	■	■						
	VXF42..		■			16	F	■	■		■			■	■	■						
	VVF43..	■				16	F	■	■	■	■	■		■	■	■	■	■	■			
	VXF43..		■			16	F	■	■	■	■	■		■	■	■			■			
	VVF53..	■				25	F	■	■	■	■	■		■	■	■	■	■	■			
	VXF53..		■			25	F	■	■	■	■	■		■	■	■			■			
	VVF61..	■				40	F		■	■	■	■		■	■	■	■	■	■			
	VXF61..		■			40	F		■	■	■	■		■	■	■			■			
PICV	VPD../VPE..	■				10	ET		■		■			■		■						
	VPP46..	■				25	ET		■		■			■		■						
	VPI46..	■				25	IT		■		■			■		■						
	VPF43..	■				16	F	■	■		■			■		■						
	VPF53..	■				25	F	■	■		■			■		■						
Control ball valves	VAG61..	■				40	ET	■	■		■			■	■	■						
	VBG61..		■			40	ET	■	■		■			■	■	■						
	VAI61..	■				40	IT	■	■		■			■	■	■						
	VBI61..		■			40	IT	■	■		■			■	■	■						
	VWG41..				■	16	ET/IT	■	■		■			■	■	■						
Magnetic valves	MXG461..	■	■			16	ET		■		■			■		■						
	MXG461..P	■	■			16	ET		■							■			■			
	MXG461B..	■	■			16	ET			■	■	■	■	■		■						
	MXG461S..	■	■			16	ET		■	■	■	■	■	■		■						
	MXG462S..	■	■			16	ET		■	■	■	■	■	■		■						
	MXF461..	■	■			16	F		■		■			■		■						
	MXF461..P	■	■			16	F		■									■		■		
	M3P..FY	■	■			16	F		■		■			■		■						
	M3P..FYP	■	■			16	F											■		■		
	MVF461H..	■				16	F		■		■			■	■	■	■	■				
Rotary valves	VBF21..		■			6	F							■	■	■						
	VKF41..	■				16	F		■		■			■	■	■						
	VKF46..	■				16	F		■	■	■			■		■						
	VAG60..	■				40	ET	■	■		■			■	■	■						
	VBG60..		■			40	ET	■	■		■			■	■	■						
	VAI60..	■				40	IT	■	■		■			■	■	■						
	VBI60..		■			40	IT	■	■		■			■	■	■						
Refrigerant valves	M2FP03GX					32	-		■												■	■
	M3FK..LX..		■			32	S		■												■	■
	M3FB..LX..		■			PS 43	S		■												■	■
	MVL661..	■				PS 45	S															
	MVS661..N	■				63	W/S		■												■	■

Recommendation: water treatment according to VDI 2035

¹⁾ Open circuits; ²⁾ Not for drinking water circuit (open circuit) ³⁾ Variable air volume; ⁴⁾ Sealed bypass; ⁵⁾ As zone valve for floor heating systems; IT = internally

Permissible medium temperature [°C]															Generation				Distribution			Consumption / Use								
-40	-25	-20	-10	0	1	...	90	100	110	120	130	150	180	220	District heating	Boiler plants	Chiller plants	Cooling towers ¹⁾	Domestic hot water ²⁾	Heating groups	Air handling units	Floor heating	Radiators	Chilled ceilings	Heated and chilled ceilings	VAV ³⁾	Fan coil units	Zone control		
																													VDN../VEN../VUN..	Globe valves
																													VD1..CLC	
																													VVP45..	
																													VXP45..	
																													VMP45..	
																													VVP47..	
																													VXP47..	
																													VMP47..	
																													VVG41..	
																													VXG41..	
																													VXG41..01 ⁴⁾	
																													VVG44..	
																													VXG44..	
																													VVG549..	
																													VVI46../2	
																													VXI46../2	
																													VVF22..	
																													VXF22..	
																													VVF32..	
																													VXF32..	
																													VVF42..	
																													VXF42..	
																													VVF43..	
																													VVF43..	
																													VVF53..	
																													VXF53..	
																													VVF61..	
																													VXF61..	
																													VPD../VPE..	PICV
																													VPP46..	
																													VPI46..	
																													VPF43..	
																													VPF53..	
																													VAG61..	Control ball valves
																													VBG61..	
																													VAI61..	
																													VBI61..	
																													VWG41..	
																													MXG461..	Magnetic valves
																													MXG461..P	
																													MXG461B..	
																													MXG461S..	
																													MXG462S..	
																													MXF461..	
																													MXF461..P	
																													M3P..FY	
																													M3P..FYP	
																													MVF461H..	
																													VBF21..	Refrigerant valves
																													VKF41..	
																													VKF46..	
																													VAG60..	
																													VBG60..	
																													VAI60..	
																													VBI60..	
																													M2FP03GX	
																													M3FK..LX..	
																													M3FB..LX..	
																													MVL661..	
																													MVS661..N	

threaded connection, ET = externally threaded connection, F = flanged connection, S = soldered connection, W = welded connection

Threaded globe valves

Typical applications – Radiators	Actuators RTN..	Data sheet N2111							
						RTN51/RTN51G	RTN71	RTN81	
Typical applications – Radiators	Actuators STA.. SSA..	Data sheet N4884 N4893				4.5 mm 100 N	2.5 mm 100 N	4.5 mm 90 N	
									
	Operating voltage	Positioning signal	Positioning time [s]						
	AC 230 V	2-position	210	STA23	–	STA23HD ¹⁾			
		3-position	150	–	SSA31	–			
	AC 24 V	3-position	150	–	SSA81	–			
		0...10 V	270 ²⁾	STA63	–	–			
	AC/DC 24 V	2-position/PDM	270	STA73	–	STA73HD ¹⁾			
		0...10 V	34	–	SSA61	–			
	Normally Open / Normally Closed (for radiator valves)				NC	–	NC		
PN 10	1...120 °C	DIN	NF	DN	Rp/R [Inch]	k _v [m³/h]	Δp _{max} [kPa]	Δp _{max} [kPa]	Δp _{max} [kPa]
Data sheet	N2105	N2106							
		VDN110	VDN210	10	Rp/R ⅜	0.09...0.63	60	60	60
		VDN115	VDN215	15	Rp/R ½	0.10...0.89	60	60	60
		VDN120	VDN220	20	Rp/R ¾	0.31...1.41	60	60	60
		VEN110	VEN210	10	Rp/R ⅜	0.09...0.63	60	60	60
		VEN115	VEN215	15	Rp/R ½	0.10...0.89	60	60	60
		VEN120	VEN220	20	Rp/R ¾	0.31...1.41	60	60	60
		–	VUN210	10	Rp/R ⅜	0.14...0.60	60	60	60
		–	VUN215	15	Rp/R ½	0.13...0.77	60	60	60

Presettings for radiator valves VEN.., VDN.., VUN..

k_v values [m³/h] at the different preadjusted positions (XP = 2K)

Control range with electromotoric and electrothermic actuators SSA.., STA..		■	■	■	■	■	■	–
Control range with thermostatic head RTN..		■	■	■	■	■	■	■
Reference numbers for preadjustment		1	2	3	4	5	N	N (k _{vs})
VDN110/VDN210/VEN110/VEN210		0.072	0.17	0.24	0.28	0.37	0.43	0.63
VDN115/VDN215/VEN115/VEN215		0.07	0.17	0.28	0.36	0.45	0.50	0.89
VDN120/VDN220/VEN120/VEN220		0.22	0.35	0.44	0.52	0.60	0.71	1.41
VUN210		0.14	0.26	0.34	0.39	0.40	0.43	0.60
VUN215		0.13	0.22	0.30	0.39	0.45	0.50	0.77

Threaded globe valves

Typical applications	Actuators	Data sheet			4.5 mm	2.5 mm	
	– Chilled ceilings	STA.. SSA..	N4884 N4893				
		Operating voltage	Positioning signal	Positioning time [s]			
		AC 230 V	2-position	210	STA23	–	
			3-position	150	–	SSA31	
		AC 24 V	3-position	150	–	SSA81	
			0...10 V	270 ²⁾	STA63	–	
		AC/DC 24 V	2-position/PDM	270	STA73	–	
			0...10 V	34	–	SSA61	
	Normally Open / Normally Closed (for radiator valves)				NC	–	
PN 10	1...110 °C		DN	Rp/R [Inch]	k _v [l/h]	Δp _{max} [kPa]	Δp _{max} [kPa]
Data sheet		N2103					
	VD115CLC	15	Rp/R ½	0.25...1.9	150	150	
	VD120CLC	20	Rp/R ¾	0.25...2.6	150	150	
	VD125CLC	25	Rp/R 1	0.25...2.6	150	150	

¹⁾ Optimized for floor heating systems

²⁾ In control mode (warm-up time) min. running time approx. 30 s/mm

k_v = nominal flow rate of cold water (5...30 °C) through the valve at the respective stroke and a differential pressure of 100 kPa (1 bar)

The selected kv values of the radiator valves can be easily and precisely set on the valve head in 5 steps + N (fully open).

Threaded globe valves

Typical applications		Actuators	Data sheet			5.5 mm									
– Floor heating – Chilled ceilings – VAV – Fan coil units – Zone control		SSB..	N4891			200 N		200 N							
		Operating voltage	Positioning signal	Positioning time [s]	Auxiliary switch										
					SSB..1.1										
					AC 230 V					3-position	150	✓			
					AC 24 V					3-position	150	✓			
AC/DC 24 V	0...10 V	75	–	SSB61	–										
PN 16	1...110 °C	DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]							
Data sheet	N4845														
	VVP45.10-.. ¹)	10	G ½B	0.25 / 0.4 / 0.63 / 1 / 1.6	725	400	725	400							
	VVP45.15-2.5	15	G ¾B	2.5	350	350	350	350							
	VVP45.20-4	20	G 1B	4	350	350	350	350							
	VVP45.25-6.3	25	G 1¼B	6.3	300	300	300	300							
	VXP45.10-..	10	G ½B	0.25 / 0.4 / 0.63 / 1 / 1.6	–	400	–	400							
	VXP45.15-2.5	15	G ¾B	2.5	–	350	–	350							
	VXP45.20-4	20	G 1B	4	–	350	–	350							
	VXP45.25-6.3	25	G 1¼B	6.3	–	300	–	300							
	VMP45.10-..	10	G ½B	0.25 / 0.4 / 0.63 / 1	–	400	–	400							
	VMP45.10-1.6	10	G ½B	1.6	–	400	–	400							
	VMP45.15-2.5	15	G ¾B	2.5	–	350	–	350							
	VMP45.20-4	20	G 1B	4	–	350	–	350							
Typical applications		Actuators	Data sheet			4.5 mm		2.5 mm							
– Chilled ceilings – VAV – Fan coil units		STP..	N4884			100 N		135 N		160 N					
		SFP..	N4865												
		SSP..	N4864												
		Operating voltage	Positioning signal	Positioning time [s]	Spring return function [s]	STP23		–		–					
												AC 230 V	2-position	210	–
													2-position	10	30–50
			3-position	150	–	–	–	–	–						
		AC 24 V	2-position	10	30–50	–	SFP71/18	–							
			3-position	43	–	–	–	SSP81.04							
			3-position	150	–	–	–	SSP81							
0...10 V	270 ²)		–	STP63	–	–									
AC/DC 24 V	2-position/PDM		270	–	STP73	–	–								
	0...10 V	34	–	–	–	SSP61									
PN 16	1...110 °C	DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]					
Data sheet	N4847														
	VVP47.10-.. ¹)	10	G ½B	0.25 / 0.4	700	400	1000	400	1000	400					
	VVP47.10-..	10	G ½B	0.63 / 1	250	250	500	400	500	400					
	VVP47.10-1.6	10	G ½B	1.6	150	150	300	300	300	300					
	VVP47.15-2.5	15	G ¾B	2.5	150	150	300	300	300	300					
	VVP47.20-4	20	G 1B	4	100	100	175	175	175	175					
	VXP47.10-..	10	G ½B	0.25 / 0.4	–	400	–	400	–	400					
	VXP47.10-..	10	G ½B	0.63 / 1	–	250	–	400	–	400					
	VXP47.10-1.6	10	G ½B	1.6	–	150	–	300	–	300					
	VXP47.15-2.5	15	G ¾B	2.5	–	150	–	300	–	300					
	VXP47.20-4	20	G 1B	4	–	100	–	175	–	175					
	VMP47.10-..	10	G ½B	0.25 / 0.4	–	400	–	400	–	400					
	VMP47.10-..	10	G ½B	0.63 / 1	–	250	–	400	–	400					
	VMP47.10-1.6	10	G ½B	1.6	–	150	–	300	–	300					
	VMP47.15-2.5	15	G ¾B	2.5	–	150	–	300	–	300					

Union nuts for threaded valves

Union nuts for threaded valves See page 9

VVP45..N with Serto compression fittings, $k_{vs} = 2.5 / 4 / 6.3 \text{ m}^3/\text{h}$

VVP45..S, VMP45..S with Conex® compression fittings, $k_{vs} = 0.63 / 1 / 1.6 / 2.5 \text{ m}^3/\text{h}$

VVP47..S, VMP47..S with Conex® compression fittings, $k_{vs} = 0.63 / 1 / 1.6 / 2.5 \text{ m}^3/\text{h}$

¹⁾ .. = k_{vs} value

²⁾ In control mode (warm-up time) min. running time approx. 30 s/mm

Threaded globe valves

Typical applications	Actuators	Data sheet			2.5 mm		4.5 mm	2.5 mm
– Floor heating – Fan coil units – Zone control	SFA.. SUA21/1 STA.. SSA31.04 ¹⁾	N4863 N4830 N4884 N4860			200 N	170 N	100 N	160 N
								
	Operating voltage	Positioning signal	Positioning time [s]	Spring return function [s]				
	AC 230 V	2-position	10	30–50	SFA21/18	–	–	–
		2-position	210	–	–	–	STA23	–
		2-position/SPST ²⁾	10	–	–	SUA21/3	–	–
		3-position/SPDT ²⁾	43	–	–	–	–	SSA31.04
	AC 24 V	2-position	10	30–50	SFA71/18	–	–	–
		0...10 V	270 ³⁾	–	–	–	STA63	–
	AC/DC 24 V	2-position/PDM	270	–	–	–	STA73	–
PN 16	1...110 °C							
Data sheet	N4842	DN	Rp [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]
	VVI46.15/2	15	Rp ½	2	300	300	400	400
	VVI46.20/2	20	Rp ¾	3.5	300	300	400	400
	VVI46.25/2	25	Rp 1	5	250	250	250	250
	VXI46.15/2 ⁴⁾	15	Rp ½	2	–	300	–	400
	VXI46.20/2 ⁴⁾	20	Rp ¾	3.5	–	300	–	400
	VXI46.25/2 ⁴⁾	25	Rp 1	5	–	250	–	250
	VXI46.25T ⁵⁾	25	Rp 1	5	–	200	–	200

Thermal actuators and connecting cables for combinable range, STx..3..

Color		White						Black
Equipped with		–	Function module DC 0...10 V		Auxiliary switch for STA	Auxiliary switch for STP	LED	–
Positioning signal		2-position (On/Off)	DC 0...10 V	DC 0...10 V	2-position (On/Off)	2-position (On/Off)	2-position (On/Off)	2-position (On/Off)
		[STA..., NC]	[STA..., NC]	–	[STA..., NC]	–	[STA..., NC]	[STA..., NC]
		[STP..., NO]	–	[STP..., NO]	–	[STP..., NO]	[STP..., NO]	[STP..., NO]
Standard PVC cables	1 m				ASA23U10	ASP23U10		
	2 m	ASY23L20	ASY6AL20	ASY6PL20			ASY23L20LD	
	3 m							ASY23L30B
	5 m	ASY23L50						ASY23L50B
	10 m	ASY23L100						
	15 m	ASY23L150						
Halogen-free cables	2 m	ASY23L20HF	ASY6AL20HF	ASY6PL20HF				
	5 m	ASY23L50HF						
	10 m	ASY23L100HF						
Actuator								
STA73/00		■	■		■		■	
STA23/00		■			■			
STP73/00		■		■		■	■	
STP23/00		■				■		
STA73PR/00 ⁶⁾		■			■		■	
STP73PR/00 ⁶⁾		■				■	■	
STA73MP/00 ⁷⁾		■	■		■		■	
STA23MP/00 ⁷⁾		■			■			
STA73B/00								■
STA23B/00								■

¹⁾ Not suited for radiator valves

²⁾ SPST = single-pole single-throw, SPDT = single-pole double-throw

³⁾ In control mode (warm-up time) min. running time approx. 30 s/mm

⁴⁾ 70% k_{vs} in bypass, leakage rate in bypass 2...5% of k_{vs} value

⁵⁾ 100% k_{vs} in bypass, leakage rate in bypass 0.05% of k_{vs} value. **For noiseless operation, the value of 100 kPa should not be exceeded.**

⁶⁾ Actuators ideal for parallel running. Pulse duration modulation (PDM) in connection with Siemens room controllers of the Desigo™ range and room thermostats.



⁷⁾ Multipack with 50 actuators (OEM) NC: normally closed, NO: normally open

Threaded globe valves

Typical applications		Actuators	Data sheet		Spring return function [s]			20 mm						
– District heating – Boiler plants – Chiller plants – Domestic hot water – Heating groups – Air handling units		SAX..	N4501					800 N	1000 N	2800 N				
		SKD..	N4561											
		SKB..	N4564											
		Operating voltage	Positioning signal	Positioning time [s]										
				SAX	SKD	SKB	SKD	SKB						
		AC 230 V	3-position	120	120	120	–	–	SAX31.00	SKD32.50	SKB32.50			
			3-position	–	120	120	8	10	–	SKD32.51	SKB32.51			
			3-position	30	–	–	–	–	SAX31.03	–	–			
			3-position	–	30	–	8	–	–	SKD32.21	–			
		AC 24 V ¹⁾	3-position	120	120	120	–	–	SAX81.00	SKD82.50	SKB82.50			
			3-position	–	120	120	8	10	–	SKD82.51	SKB82.51			
			3-position	30	–	–	–	–	SAX81.03	–	–			
			0...10 V, 4...20 mA	–	30	120	–	–	–	SKD60	SKB60			
			0...10 V, 4...20 mA	–	30	120	15	10	–	SKD62	SKB62			
AC/DC 24 V		0...10 V, 4...20 mA	30	–	–	–	–	SAX61.03	–	–				

PN 16	-25...150 °C ²⁾			DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	
Data sheet	N4363		N4463										
 	VVG41.11..12	 	–	–	15	G 1 B	0.63 / 1	1600	800	1600	800	1600	800
 	VVG41.13		–	VXG41.1301	15	G 1 B	1.6	1600	800	1600	800	1600	800
	VVG41.14		–	VXG41.1401	15	G 1 B	2.5	1600	800	1600	800	1600	800
	VVG41.15		–	VXG41.1501	15	G 1 B	4	1600	800	1600	800	1600	800
	VVG41.20		–	VXG41.2001	20	G 1 1/4 B	6.3	1600	800	1600	800	1600	800
	VVG41.25		–	VXG41.2501	25	G 1 1/2 B	10	1550	800	1600	800	1600	800
	VVG41.32		–	VXG41.3201	32	G 2 B	16	875	800	1275	800	1600	800
	VVG41.40		–	VXG41.4001	40	G 2 1/4 B	25	525	525	775	775	1600	800
VVG41.50		–	VXG41.5001	50	G 2 3/4 B	40	300	300	450	450	1225	800	

Union nuts for threaded valves ³⁾

	Type		G [Inch]	R, Rp [Inch]	Material
	Set of 2	Set of 3			
	ALG132	ALG133	G ½B	R ⅜ (Externally threaded)	Brass
	ALG142	ALG143	G ¾B	R ½ (Externally threaded)	Brass
	ALG122	ALG123	G ¾B	Rp ⅜	Malleable cast iron
	ALG152	ALG153	G 1B	Rp ½	Malleable cast iron
	ALG152B	ALG153B	G 1B	Rp ½	Brass
	ALG202	ALG203	G 1¼B	Rp ¾	Malleable cast iron
	ALG202B	ALG203B	G 1¼B	Rp ¾	Brass
	ALG252	ALG253	G 1½B	Rp 1	Malleable cast iron
	ALG252B	ALG253B	G 1½B	Rp 1	Brass
	ALG322	ALG323	G 2B	Rp 1¼	Malleable cast iron
	ALG322B	ALG323B	G 2B	Rp 1¼	Brass
	ALG402	ALG403	G 2¼B	Rp 1½	Malleable cast iron
	ALG402B	ALG403B	G 2¼B	Rp 1½	Brass
ALG502	ALG503	G 2¾B	Rp 2	Malleable cast iron	
ALG502B	ALG503B	G 2¾B	Rp 2	Brass	
	Type		G [Inch]	Ø d [mm]	Material
	Set of 2				
	ALS152		G ¾B	21.3	Steel, weldable
	ALS202		G 1B	26.8	Steel, weldable
	ALS252		G 1¼B	33.7	Steel, weldable

¹⁾ SAX81...: AC/DC 24 V

²⁾ SAX.. max. 130 °C

³⁾ Valve side: cylindrical thread G according to ISO 228-1, pipe side: ALG.. with cylindrical Rp- or tapered R-thread according to ISO 7-1 Pipe side: ALS.. with welded connection

Threaded globe valves

Typical applications		Actuators		Data sheet			5.5 mm					
– Boiler plants – Domestic hot water – Heating groups – Air handling unit		SAS..		N4581			400 N 	400 N 	400 N 			
		Operating voltage		Positioning signal	Positioning time [s]	Spring return function [s]						
		AC 230 V		3-position	120	–	SAS31.00	–	–			
				3-position	30	–	SAS31.03	–	–			
				3-position	120	28	–	SAS31.50	–			
				3-position	30	14	–	SAS31.53	–			
		AC/DC 24 V		0...10 V, 4...20 mA, 0...1000 Ω	30	–	SAS61.03	–	–			
					30	14	–	–	SAS61.33			
					30	14	–	SAS61.53	–			
				3-position	120	–	SAS81.00	–	–			
3-position	30			–	SAS81.03	–	–					
3-position	30			14	–	–	SAS81.33					
PN 16	1...120 °C			DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]
Data sheet	N4364		N4464									
	VVG44.15-.. ¹⁾		VXG44.15-..	15	G 1 B	0.25 / 0.4 / 0.63	1600	400	1600	400	1600	400
	VVG44.15-..		VXG44.15-..	15	G 1 B	1 / 1.6	725	400	725	400	725	400
	VVG44.15-..		VXG44.15-..	15	G 1 B	2.5 / 4	400	400	400	400	400	400
	VVG44.20-6.3		VXG44.20-6.3	20	G 1¼B	6.3	750	400	750	400	750	400
	VVG44.25-10		VXG44.25-10	25	G 1½B	10	400	400	400	400	400	400
	VVG44.32-16		VXG44.32-16	32	G 2 B	16	250	250	250	250	250	250
	VVG44.40-25		VXG44.40-25	40	G 2¼B	25	125	125	125	125	125	125

Typical applications		Actuators		Data sheet			5.5 mm					
– Boiler plants – Heating groups – Air handling units		SSC..		N4895			300 N 					
		Operating voltage		Positioning signal	Positioning time [s]	Spring return function [s]						
		AC 230 V		3-position	150	–	SSC31					
		AC 24 V		3-position	150	–	SSC81					
		AC/DC 24 V		0...10 V	30	–	SSC61					
				0...10 V	30	30	SSC61.5					
PN 16	1...110 °C			DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]		Δp _{max} [kPa]			
Data sheet	N4845		N4845									
	VVP45.20-4		VXP45.20-4	20	G 1 B	4	350		350			
	VVP45.25-6.3		VXP45.25-6.3	25	G 1¼B	6.3	300		300			
	VVP45.25-10		VXP45.25-10	25	G 1½B	10	300		300			
	VVP45.32-16		VXP45.32-16	32	G 2 B	16	175		175			
	VVP45.40-25		VXP45.40-25	40	G 2¼B	25	75		75			

Typical applications		Actuators		Data sheet			5.5 mm					
– District heating – Boiler plants		SAT..		N4584			300 N 	300 N 				
		Operating voltage		Positioning signal	Positioning time [s]	Spring return function [s]						
		AC 230 V		3-position	8	–	SAT31.008	–				
				3-position	15	8	–	SAT31.51				
		AC/DC 24 V		0...10 V, 4...20 mA, 0...1000 Ω	8	–	SAT61.008	–				
					15	8	–	SAT61.51				
PN 25	1...130 °C			DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
Data sheet	N4380											
	VVG549.15-.. ¹⁾			15	G ¾B	0.25 / 0.4 / 0.63	2500	1200	2500	1200		
	VVG549.15-..			15	G ¾B	1 / 1.6 / 2.5	2000	1200	2000	1200		
	VVG549.20-4K			20	G 1 B	5	1600	1200	1600	1200		
	VVG549.25-6.3K			25	G 1¼B	6.3	1600	1200	1600	1200		

¹⁾ .. = insert k_{vs} value

Flanged globe valves

Typical applications		Actuators		Data sheet				Spring return function [s]	20 mm		40 mm			
– District heating		SAX..		N4501					800 N	1000 N	2800 N	2800 N		
– Boiler plants		SKD..		N4561										
– Chiller plants		SKB..		N4564										
– Domestic hot water		SKC..		N4566										
– Heating groups														
– Air handling units														
		Operating voltage	Positioning signal	Positioning time [s]										
				SAX	SKD	SKB/C	SKD	SKB/C						
AC 230 V		3-position		120	120	120	–	–	SAX31.00	SKD32.50	SKB32.50	SKC32.60		
		3-position		–	120	120	8	10/18	–	SKD32.51	SKB32.51	SKC32.61		
		3-position		30	–	–	–	–	SAX31.03	–	–	–		
AC 24 V ¹⁾		3-position		–	30	–	8	–	–	SKD32.21	–	–		
		3-position		120	120	120	–	–	SAX81.00	SKD82.50	SKB82.50	SKC82.60		
		3-position		–	120	120	8	10/18	–	SKD82.51	SKB82.51	SKC82.61		
		3-position		30	–	–	–	–	SAX81.03	–	–	–		
		0...10 V, 4...20 mA		–	30	120	–	–	–	SKD60	SKB60	SKC60		
AC/DC 24 V		0...10 V, 4...20 mA		–	30	120	15	10/20	–	SKD62	SKB62	SKC62		
		0...10 V, 4...20 mA		30	–	–	–	–	SAX61.03	–	–	–		
PN 6		-10...130 °C				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
Data sheet		N4401				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
		VVF22.25-.. ²⁾		VXF22.25-..	25	2.5/4/6.3/10	600	300	600	300	600	300	–	–
		VVF22.40-..		VXF22.40-..	40	16/25	550	300	600	300	600	300	–	–
		VVF22.50-40		VXF22.50-40	50	40	350	300	450	300	600	300	–	–
		VVF22.65-63		VXF22.65-63	65	63	200	150	250	200	600	300	–	–
		VVF22.80-100		VXF22.80-100	80	100	125	75	175	125	450	300	–	–
		VVF22.100-160		VXF22.100-160	100	160	–	–	–	–	–	–	300	250
PN 10		-10...150 °C ³⁾				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
Data sheet		N4402				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
		VVF32.15-.. ²⁾		VXF32.15-..	15	1.6/2.5/4	1000	400	1000	400	1000	400	–	–
		VVF32.25-..		VXF32.25-..	25	6.3/10	1000	400	1000	400	1000	400	–	–
		VVF32.40-..		VXF32.40-..	40	16/25	550	400	750	400	1000	400	–	–
		VVF32.50-40		VXF32.50-40	50	40	350	300	450	400	1000	400	–	–
		VVF32.65-63		VXF32.65-63	65	63	200	150	250	200	700	400	–	–
		VVF32.80-100		VXF32.80-100	80	100	125	75	175	125	450	400	–	–
		VVF32.100-160		VXF32.100-160	100	160	–	–	–	–	–	–	300	250
		VVF32.125-250		VXF32.125-250	125	250	–	–	–	–	–	–	190	160
PN 16		-10...150 °C ³⁾				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
Data sheet		N4403				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
		VVF42.15-.. ²⁾		VXF42.15-..	15	1.6/2.5/4	1600	400	1600	400	1600	400	–	–
		VVF42.20-6.3		VXF42.20-6.3	20	6.3	1600	400	1600	400	1600	400	–	–
		VVF42.25-..		VXF42.25-..	25	6.3/10	1600	400	1600	400	1600	400	–	–
		VVF42.32-16		VXF42.32-16	32	16	900	400	1200	400	1600	400	–	–
		VVF42.40-..		VXF42.40-..	40	16/25	550	400	750	400	1600	400	–	–
		VVF42.50-..		VXF42.50-..	50	31.5/40	350	300	450	400	1200	400	–	–
		VVF42.65-..		VXF42.65-..	65	50/63	200	150	250	200	700	400	–	–
		VVF42.80-..		VXF42.80-..	80	80/100	125	75	175	125	450	400	–	–
		VVF42.100-..		VXF42.100-..	100	125/160	–	–	–	–	–	–	300	250
		VVF42.125-..		VXF42.125-..	125	200/250	–	–	–	–	–	–	190	160
		VVF42.150-..		VXF42.150-..	150	315/400	–	–	–	–	–	–	125	100
		VVF42.50-40K		–	50	40	1600	400	1600	400	1600	400	–	–
		VVF42.65-63K		–	65	63	1600	400	1600	400	1600	400	–	–
		VVF42.80-100K		–	80	100	1600	400	1600	400	1600	400	–	–
		VVF42.100-160K		–	100	160	–	–	–	–	–	–	1600	400
VVF42.125-250K	–	125	250	–	–	–	–	–	–	1600	400			
VVF42.150-360K	–	150	360	–	–	–	–	–	–	1600	400			
PN 16		-20...220 °C				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
Data sheet		N4404				DN	k _{vs} [m³/h]		Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]		
		VVF43.65-50		–	65	50	–	–	–	–	–	700	650	
		VVF43.65-63		VXF43.65-63	65	63	–	–	–	–	–	–	700	650
		VVF43.80-80		–	80	80	–	–	–	–	–	–	450	400
		VVF43.80-100		VXF43.80-100	80	100	–	–	–	–	–	–	450	400
		VVF43.100-125		–	100	125	–	–	–	–	–	–	300	250
		VVF43.100-160		VXF43.100-160	100	160	–	–	–	–	–	–	300	250
		VVF43.125-200		–	125	200	–	–	–	–	–	–	190	160
		VVF43.125-250		VXF43.125-250	125	250	–	–	–	–	–	–	190	160
		VVF43.150-315		–	150	315	–	–	–	–	–	–	125	100
		VVF43.150-400		VXF43.150-400	150	400	–	–	–	–	–	–	125	100
		VVF43.65-63K		–	65	63	–	–	–	–	–	–	1600	800
		VVF43.80-100K		–	80	100	–	–	–	–	–	–	1600	800
		VVF43.100-150K		–	100	150	–	–	–	–	–	–	1600	800
		VVF43.125-220K		–	125	220	–	–	–	–	–	–	1600	800
		VVF43.150-315K		–	150	315	–	–	–	–	–	–	1600	800
VVF43.200-450K	–	200	450	–	–	–	–	–	–	1200	800			
VVF43.250-630K	–	250	630	–	–	–	–	–	–	1000	800			

¹⁾ SAX81...: AC/DC 24 V

2) .. = insert k_{ys} value

³⁾ SAX.. max. 130 °C; VVF43.., VXF43..: For DN 15...50 and k_{vs} values $\leq 40 \text{ m}^3/\text{h}$ see V..F53..

Flanged globe valves

Typical applications		Actuators		Data sheet				Spring return function [s]	20 mm				40 mm		
District heating Boiler plants Chiller plants Domestic hot water Heating groups Air handling units		SAX.. SKD.. SKB.. SKC..		N4501 N4561 N4564 N4566											
		Operating voltage	Positioning signal	Positioning time [s]											
				SAX	SKD	SKB/C	SKD		SKB/C						
AC 230 V		3-position	120	120	120	–	–	SAX31.00	SKD32.50	SKB32.50	SKC32.60				
		3-position	–	120	120	8	10/18	–	SKD32.51	SKB32.51	SKC32.61				
		3-position	30	–	–	–	–	SAX31.03	–	–	–				
		3-position	–	30	–	8	–	–	SKD32.21	–	–				
AC 24 V ¹⁾		3-position	120	120	120	–	–	SAX81.00	SKD82.50	SKB82.50	SKC82.60				
		3-position	–	120	120	8	10/18	–	SKD82.51	SKB82.51	SKC82.61				
		3-position	30	–	–	–	–	SAX81.03	–	–	–				
		0...10 V, 4...20 mA	–	30	120	–	–	–	SKD60	SKB60	SKC60				
		0...10 V, 4...20 mA	–	30	120	15	10/20	–	SKD62	SKB62	SKC62				
AC/DC 24 V		0...10 V, 4...20 mA	30	–	–	–	–	SAX61.03	–	–	–				
PN 25	-20...220 °C ²⁾			DN	k_{vs} [m³/h]			Δp_s [kPa]	Δp_{max} [kPa]	Δp_s [kPa]	Δp_{max} [kPa]	Δp_s [kPa]	Δp_{max} [kPa]		
Data sheet	N4405		N4405												
				–	15	0.16/0.2/0.25/ 0.32/0.4/0.5/0.63		2500	1200	2500	1200	2500	1200	–	–
				–	15	0.8/1/1.25/2/3.2		2500	1200	2500	1200	2500	1200	–	–
				VXF53.15-..	15	1.6/2.5/4		2500	1200	2500	1200	2500	1200	–	–
				VXF53.20-6.3	20	6.3		2500	1200	2500	1200	2500	1200	–	–
				–	25	5/8		1600	1200	2100	1200	2500	1200	–	–
				VXF53.25-..	25	6.3/10		1600	1200	2100	1200	2500	1200	–	–
				VXF53.32-16	32	16		900	750	1200	1100	2500	1200	–	–
				–	40	12.5/20		550	500	750	650	2000	1200	–	–
				VXF53.40-..	40	16/25		550	500	750	650	2000	1200	–	–
				–	50	31.5		350	300	450	400	1200	1150	–	–
				VXF53.50-40	50	40		350	300	450	400	1200	1150	–	–
				VXF53.65-63	65	63		–	–	–	–	–	–	700	650
				VXF53.80-100	80	100		–	–	–	–	–	–	450	400
				VXF53.100-160	100	160		–	–	–	–	–	–	300	250
				VXF53.125-250	125	250		–	–	–	–	–	–	190	160
				VXF53.150-400	150	400		–	–	–	–	–	–	125	100
				–	50	36		–	–	2500	1250	2500	1250	–	–
				–	65	63		–	–	–	–	–	–	2500	1250
				–	80	100		–	–	–	–	–	–	2500	1250
				–	100	150		–	–	–	–	–	–	2500	1250
				–	125	220		–	–	–	–	–	–	2500	1250
				–	150	315		–	–	–	–	–	–	2500	1250
				–	200	450		–	–	–	–	–	–	1200	800
				–	250	630		–	–	–	–	–	–	1200	800
PN 40	-25...220 °C			DN	k_{vs} [m³/h]			Δp_s [kPa]	Δp_{max} [kPa]	Δp_s [kPa]	Δp_{max} [kPa]	Δp_s [kPa]	Δp_{max} [kPa]	Δp_s [kPa]	Δp_{max} [kPa]
Data sheet	N4382		N4482												
				–	15	0.19/0.3/0.45		–	–	4000	1600	4000	1600	–	–
				–	15	0.7/1.2		–	–	4000	1600	4000	1600	–	–
				VXF61.14..15 ⁴⁾	15	1.9/3		–	–	4000	1600	4000	1600	–	–
				VXF61.24..25 ⁴⁾	25	3/5/7.5 5/7.5		–	–	2250	1600	4000	1600	–	–
				VXF61.39..40 ⁴⁾	40	12/19		–	–	–	–	4000	1600	–	–
				VXF61.49..50 ⁴⁾	50	19/31		–	–	–	–	4000	1600	–	–
				VXF61.65	65	49		–	–	–	–	–	–	4000	1000
				VXF61.80	80	78		–	–	–	–	–	–	4000	700
				VXF61.90	100	124		–	–	–	–	–	–	4000	450
				VXF61.91	125	200		–	–	–	–	–	–	4000	300
				VXF61.92	150	300		–	–	–	–	–	–	4000	200
								–	–	–	–	–	–	–	125

¹⁾ SAX81...: AC/DC 24 V

²⁾ SAX... max. 130 °C

³⁾ .. = insert k_{vs} value

⁴⁾ For 09...15, 14...15, 23...25, 24...25, 39...40, 49...50 = insert number in place of k_{vs} value


Threaded pressure independent combi valves (PICV)

Typical applications – Radiators – Chilled ceilings – Fan coil units	Actuators		Data sheet						4.5 mm		2.5 mm			
	RTN..		N2111						100 N		100 N			
	STA..		N4884											
	SSA..		N4893											
	Operating voltage	Positioning signal	Positioning time [s]											
	AC 230 V	2-position	210						–	STA23	–			
		3-position	150						–	–	SSA31			
	AC 24 V	3-position	150						–	–	SSA81			
		0...10 V	270 ¹⁾						–	STA63	–			
	AC/DC 24 V	2-position/PDM	270						–	STA73	–			
0...10 V		34					–	–	SSA61					
							RTN51	–	–					
							RTN71	–	–					
							RTN81	–	–					
PN 10	1...90 °C	DIN	DN	Rp/R [Inch]	V [l/h]	V _{Nom} ²⁾ [l/h]		Δp _{min} [kPa]	Δp _{max} [kPa]	Δp _{min} [kPa]	Δp _{max} [kPa]	Δp _{min} [kPa]	Δp _{max} [kPa]	
Data sheet	N2185													
		VPD110A-... ²⁾	10	Rp/R 3/8	25...318	45	90	145	6 ³⁾	200	8 ³⁾	200	10 ³⁾	200
		VPD115A-...	15	Rp/R 1/2	25...318	45	90	145	6 ³⁾	200	8 ³⁾	200	10 ³⁾	200
		VPD110B-200	10	Rp/R 3/8	95...483	200			20	200	20	200	20	200
		VPD115B-200	15	Rp/R 1/2	95...483	200			20	200	20	200	20	200
		VPE110A-...	10	Rp/R 3/8	25...318	45	90	145	6 ³⁾	200	8 ³⁾	200	10 ³⁾	200
		VPE115A-...	15	Rp/R 1/2	25...318	45	90	145	6 ³⁾	200	8 ³⁾	200	10 ³⁾	200
		VPE110B-200	10	Rp/R 3/8	95...483	200			20	200	20	200	20	200
		VPE115B-200	15	Rp/R 1/2	95...483	200			20	200	20	200	20	200
Typical applications – Heating groups – Air handling units – Chilled ceilings – VAV – Fan coil units – Zone control	Actuators		Data sheet					4.5 mm		2.5 / 5 mm		15 mm		
	STA..		N4884					100 N		100 N		200 N		
	SSA..		N4893											
	SAY..P..		A6V10628469											
	Operating voltage	Positioning signal	Positioning time [s]											
			STA	SSA	SAY									
	AC 230 V	3-position	–	150/300		30			–	SSA31	SAY31P03			
		2-position	210	–		–			STA23	–	–			
	AC 24 V	0...10 V	270 ¹⁾	–		–			STA63	–	–			
	AC/DC 24 V	3-position	–	150/300		30			–	SSA81	SAY81P03			
2-position/PDM		270	–		–			STA73	–	–				
	0...10 V	–	34/70		30			–	SSA61/SSA61EP	SAY61P03				
PN 25	1...120 °C	Without pressure testing points	With pressure testing points	DN	G [Inch]	V _{min} [l/h]	V ₁₀₀ [l/h]	Δp _{min} [kPa]	Δp _{max} [kPa]	Δp _{min} [kPa]	Δp _{max} [kPa]	Δp _{min} [kPa]	Δp _{max} [kPa]	
Data sheet	N4855													
		VPP46.10L0.2	VPP46.10L0.2Q	10	1/2	30	200	16	600	16	600	–	–	
		VPP46.10L0.4	VPP46.10L0.4Q	10	1/2	65	333	16	600	–	–	–	–	
				10	1/2	65	370	–	–	16	600	–	–	
		VPP46.15L0.2	VPP46.15L0.2Q	15	3/4	30	200	19	600	19	600	–	–	
		VPP46.15L0.6	VPP46.15L0.6Q	15	3/4	100	575	19	600	19	600	–	–	
		VPP46.20F1.4	VPP46.20F1.4Q	20	1	200	1190	22	600	–	–	–	–	
				20	1	220	1330	–	–	22	600	–	–	
		VPP46.25F1.8	VPP46.25F1.8Q	25	1 1/4	204	1470	39	600	–	–	–	–	
				25	1 1/4	250	1800	–	–	39	600	–	–	
		VPP46.32F4	VPP46.32F4Q	32	1 1/2	450	3270	28	600	–	–	–	–	
			32	1 1/2	550	4001	–	–	28	600	–	–		
PN 25	1...120 °C	Without pressure testing points	With pressure testing points	DN	Rp [Inch]	V _{min} [l/h]	V ₁₀₀ [l/h]	Δp _{min} [kPa]	Δp _{max} [kPa]	Δp _{min} [kPa]	Δp _{max} [kPa]	Δp _{min} [kPa]	Δp _{max} [kPa]	
Data sheet	N4855													
		VPI46.15L0.2	VPI46.15L0.2Q	15	1/2	30	200	19	600	19	600	–	–	
		VPI46.15L0.6	VPI46.15L0.6Q	15	1/2	100	575	19	600	19	600	–	–	
		VPI46.20F1.4	VPI46.20F1.4Q	20	3/4	200	1190	22	600	–	–	–	–	
				20	3/4	220	1330	–	–	22	600	–	–	
		VPI46.25F1.8	VPI46.25F1.8Q	25	1 1/4	204	1470	39	600	–	–	–	–	
				25	1 1/4	250	1800	–	–	39	600	–	–	
		VPI46.32F4	VPI46.32F4Q	32	1 1/2	450	3270	28	600	–	–	–	–	
				32	1 1/2	550	4001	–	–	28	600	–	–	
		–	VPI46.40F9.5Q	40	1 1/2	1370	9500	–	–	–	–	25	600	
		–	VPI46.50F12Q	50	2	1400	11500	–	–	–	–	36	600	

¹⁾ In control mode (warm-up time) min. running time approx. 30 s/mm

²⁾ .. = insert V_{nom} | V_{nom} = factory setting = volumetric flow at 0.5 mm stroke or setting mark 3 of the presetting; ³⁾ Δp_{min} is valid for V_{Nom} 45/90/145 l/h VPP46../VPI46...: Δp_{min} is for the V₁₀₀. For lower flows please consult the datasheet.

Flanged pressure independent combi valves (PICV)

Typical applications – District heating – Heating groups – Air handling units	Actuators	Data sheet					20 mm	20 / 40 mm	40 mm
	SAX..P.. SQV91P.. SAV..P..	N4509 N4833 N4510					500 N 	1100 N 	1100 N 
	Operating voltage	Positioning signal	Positioning time [s]			Spring return function [s]			
			SAX	SQV	SAV				
	AC 230 V	3-position	30	–	120	–	SAX31P03	–	SAV31P00
		3-position	–	40/80	–	30	–	SQV91P40 ¹⁾	–
		3-position	–	40/80	–	30	–	SQV91P30 ²⁾	–
	AC/DC 24 V	3-position	30	–	120	–	SAX81P03	–	SAV81P00
		3-position	–	40/80	–	30	–	SQV91P40 ¹⁾	–
		3-position	–	40/80	–	30	–	SQV91P30 ²⁾	–
0...10 V, 4...20 mA		30	–	120	–	SAX61P03	–	SAV61P00	
0...10 V, 4...20 mA		–	40/80	–	30	–	SQV91P40 ¹⁾	–	
	0...10 V, 4...20 mA	–	40/80	–	30	–	SQV91P30 ²⁾	–	
PN 16	1...120 °C		DN	V _{min} [m³/h]	V ₁₀₀ [m³/h]	Δp _{min} [kPa]	Δp _s /Δp _{max} [kPa]	Δp _s /Δp _{max} [kPa]	Δp _s /Δp _{max} [kPa]
Data sheet	N4315								
	VPF43.50F16	50	2.3	15	20	600	600	–	
	VPF43.50F25	50	4.3	25	50	600	600	–	
	VPF43.65F24	65	4.4	24	25	600	600	–	
	VPF43.65F35	65	6	35	55	600	600	–	
	VPF43.80F35	80	5.3	34	25	600	600	–	
	VPF43.80F45	80	7	43	50	600	600	–	
	VPF43.100F70	100	12.1	68	35	–	600	600	
	VPF43.100F90	100	14.8	90	75	–	600	600	
	VPF43.125F110	125	18.5	110	35	–	600	600	
	VPF43.125F135	125	23	135	53	–	600	600	
	VPF43.150F160	150	25.6	148	35	–	600	600	
	VPF43.150F200	150	32	195	65	–	600	600	
PN 25	1...120 °C		DN	V _{min} [m³/h]	V ₁₀₀ [m³/h]	Δp _{min} [kPa]	Δp _s /Δp _{max} [kPa]	Δp _s /Δp _{max} [kPa]	Δp _s /Δp _{max} [kPa]
Data sheet	N4316								
	VPF53.50F16	50	2.3	15	20	600	600	–	
	VPF53.50F25	50	4.3	25	50	600	600	–	
	VPF53.65F24	65	4.4	24	25	600	600	–	
	VPF53.65F35	65	6	35	55	600	600	–	
	VPF53.80F35	80	5.3	34	25	600	600	–	
	VPF53.80F45	80	7	43	50	600	600	–	
	VPF53.100F70	100	12.1	68	35	–	600	600	
	VPF53.100F90	100	14.8	90	75	–	600	600	
	VPF53.125F110	125	18.5	110	35	–	600	600	
	VPF53.125F135	125	23	135	53	–	600	600	
	VPF53.150F160	150	25.6	148	35	–	600	600	
	VPF53.150F200	150	32	195	65	–	600	600	

¹⁾ Fail-safe function: valve closed

²⁾ Fail-safe function: valve open

VPF43../VPF53.: Δp_{min} is for the V₁₀₀. For lower flows please consult the datasheet.

Control ball valves

Typical applications		Actuators		Data sheet			Spring return function [s]	2 Nm		5 Nm		7 Nm		10 Nm GLB 8 Nm GLD	
– Domestic hot water – Heating groups – Air handling units – Chilled ceilings – VAV – Fan coil units – Zone control		GQD..9A	N4659												
		GSD..9A	A6V10636056												
		GDB..9E	A6V10636150												
		GDB111.9E/KN	A6V10725318												
		GMA..9E	N4658												
		GLB..9E	A6V10636203												
		GLD..9E	A6V11171770												
		Operating voltage	Positioning signal	Positioning time [s]											
				G..D	G..B						GMA				
		AC 100...240 V	3-position	–	150		–				–	–	GDB341.9E	–	GLB341.9E
AC 24 V	KNX S-/LTE-Mode, KNX PL-Link	150	–	–	–	–	GDB111.9E/KN	–	–						
AC/DC 24 V	3-position	30	–	90	15	GQD131.9A	–	GMA131.9E	–						
	3-position	–	150	–	–	–	GDB141.9E	–	GLB141.9E						
	0...10 V	30	–	90	15	GQD161.9A	–	GMA161.9E	–						
	0/2...10 V	30	150	–	–	GSD161.9A	GDB161.9E	–	GLB161.9E						
	0/2...10 V	30	–	–	–	–	–	–	GLD161.9E						
PN 40	-10...120 °C														
Data sheet	N4211		N4211	DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	
				VBG61.15-.. ¹⁾	15	G 1B	1.6/2.5/4/6.3	1400	350	1400	350	1400	350	1400	350
				VBG61.15-..	15	G 1B	1	1400	350	1400	350	1400	350	1400	350
				VBG61.20-..	20	G 1¼B	4/6.3	1400	350	1400	350	1400	350	1400	350
				VBG61.20-10	20	G 1¼B	10	1400	350	1400	350	1400	350	1400	350
				VBG61.25-10	25	G 1½B	10	1400	350	1400	350	1400	350	1400	350
				VBG61.25-..	25	G 1½B	6.3/16	1400	350	1400	350	1400	350	1400	350
				–	32	G 2B	10	–	–	–	–	1000	350	1000	350
				VBG61.32-16	32	G 2B	16	–	–	–	–	1000	350	1000	350
				–	32	G 2B	25	–	–	–	–	1000	350	1000	350
				–	40	G 2¼B	16	–	–	–	–	800	350	800	350
				VBG61.40-25	40	G 2¼B	25	–	–	–	–	800	350	800	350
				–	40	G 2¼B	40	–	–	–	–	800	350	800	350
				VBG61.50-25	50	G 2¾B	25	–	–	–	–	600	350	600	350
				VBG61.50-40	50	G 2¾B	40	–	–	–	–	600	350	600	350
				VBG61.50-63	50	G 2¾B	63	–	–	–	–	600	350	600	350
PN 40	-10...120 °C														
Data sheet	N4211		N4211	DN	Rp [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	
				VBI61.15-.. ¹⁾	15	Rp ½	1.6/2.5/4/6.3	1400	350	1400	350	1400	350	1400	350
				VBI61.15-..	15	Rp ½	1/10	1400	350	1400	350	1400	350	1400	350
				VBI61.20-..	20	Rp ¾	4/6.3	1400	350	1400	350	1400	350	1400	350
				VBI61.20-10	20	Rp ¾	10	1400	350	1400	350	1400	350	1400	350
				VBI61.25-10	25	Rp 1	10	1400	350	1400	350	1400	350	1400	350
				VBI61.25-..	25	Rp 1	6.3/16	1400	350	1400	350	1400	350	1400	350
				–	32	Rp 1¼	10	–	–	–	–	1000	350	1000	350
				VBI61.32-16	32	Rp 1¼	16	–	–	–	–	1000	350	1000	350
				–	32	Rp 1¼	25	–	–	–	–	1000	350	1000	350
				–	40	Rp 1½	16	–	–	–	–	800	350	800	350
				VBI61.40-25	40	Rp 1½	25	–	–	–	–	800	350	800	350
				–	40	Rp 1½	40	–	–	–	–	800	350	800	350
				VBI61.50-25	50	Rp 2	25	–	–	–	–	600	350	600	350
				VBI61.50-40	50	Rp 2	40	–	–	–	–	600	350	600	350
				VBI61.50-63	50	Rp 2	63	–	–	–	–	600	350	600	350

¹⁾ .. = insert k_{vs} value; VBG61../VBI61...: For noiseless operation, the Δp_{max} value of 200 kPa should not be exceeded

6-port control ball valves

Typical applications			Actuators		Data sheet			2 Nm		5 Nm		5 Nm		5 Nm		
– Heated and chilled ceilings			GSD..9A		A6V10636056											
			GDB341.9E		A6V10636150											
			GDB111.9E/KN		A6V10725318											
			GDB161.9E		A6V10636150											
			Operating voltage		Positioning signal		Positioning time [s]									
							GSD	GDB								
			AC 100...240 V		2-position		–	150	–		GDB341.9E		–		–	
			AC 24 V		KNX S-/LTE-Mode, KNX PL-Link		–	150	–		–		GDB111.9E/KN		–	
			AC/DC 24 V		2-position		30	–	GSD341.9A		–		–		–	
					0/2...10 V		30	150	GSD161.9A		–		–		GDB161.9E	
PN 16	5...90 °C		DN	k _{vs} left [m³/h]	k _{vs} right [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	
Data sheet	A6V10564480															
 	VWG41.10-0.25-0.4		10	0.25	0.4	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.25-0.65		10	0.25	0.65	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.25-1.0		10	0.25	1	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.25-1.3		10	0.25	1.3	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.25-1.6		10	0.25	1.6	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.25-1.9		10	0.25	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.4-0.4		10	0.4	0.4	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.4-0.65		10	0.4	0.65	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.4-1.0		10	0.4	1	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.4-1.3		10	0.4	1.3	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.4-1.6		10	0.4	1.6	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.4-1.9		10	0.4	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.65-0.65		10	0.65	0.65	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.65-1.0		10	0.65	1	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.65-1.3		10	0.65	1.3	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.65-1.6		10	0.65	1.6	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-0.65-1.9		10	0.65	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.0-1.0		10	1	1	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.0-1.3		10	1	1.3	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.0-1.6		10	1	1.6	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.0-1.9		10	1	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.3-1.3		10	1.3	1.3	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.3-1.6		10	1.3	1.6	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.3-1.9		10	1.3	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.6-1.6		10	1.6	1.6	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.6-1.9		10	1.6	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.10-1.9-1.9		10	1.9	1.9	–	200	–	200	–	200	–	200	–	200	
	VWG41.20-0.25-2.5		20	0.25	2.5	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.25-3.45		20	0.25	3.45	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.25-4.25		20	0.25	4.25	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.4-2.5		20	0.4	2.5	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.4-3.45		20	0.4	3.45	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.4-4.25		20	0.4	4.25	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.65-2.5		20	0.65	2.5	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.65-3.45		20	0.65	3.45	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-0.65-4.25		20	0.65	4.25	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-1.0-2.5		20	1	2.5	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-1.0-3.45		20	1	3.45	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-1.0-4.25		20	1	4.25	–	–	–	200	–	200	–	200	–	200	
	VWG41.20-1.3-2.5		20	1.3	2.5	–	–	–	200	–	200	–	200	–	200	
VWG41.20-1.3-3.45		20	1.3	3.45	–	–	–	200	–	200	–	200	–	200		
VWG41.20-1.3-4.25		20	1.3	4.25	–	–	–	200	–	200	–	200	–	200		
VWG41.20-1.6-2.5		20	1.6	2.5	–	–	–	200	–	200	–	200	–	200		
VWG41.20-1.6-3.45		20	1.6	3.45	–	–	–	200	–	200	–	200	–	200		
VWG41.20-1.6-4.25		20	1.6	4.25	–	–	–	200	–	200	–	200	–	200		
VWG41.20-2.5-2.5		20	2.5	2.5	–	–	–	200	–	200	–	200	–	200		
VWG41.20-2.5-3.45		20	2.5	3.45	–	–	–	200	–	200	–	200	–	200		
VWG41.20-2.5-4.25		20	2.5	4.25	–	–	–	200	–	200	–	200	–	200		
VWG41.20-3.45-3.45		20	3.45	3.45	–	–	–	200	–	200	–	200	–	200		
VWG41.20-4.25-4.25		20	4.25	4.25	–	–	–	200	–	200	–	200	–	200		

Fittings for 6-port control ball valves

	Type	Description
	ALN15.152B	Fittings set made of brass for media temperatures up to 90 °C, consisting of
	ALN15.202B	2x cap nuts 2x inserts with external threading per ISO 228-1 2x flat seals
	ALG13.152B	Fittings set made of brass for media temperatures up to 90 °C, consisting of
	ALG15.152B	2x cap nuts with sleeves and insert per ISO 7-1
	ALG15.252B	2x flat seals

Magnetic valves										
Typical applications			Valve type		Operating voltage		Positioning signal		Type suffix	
– District heating			MXF461..		AC/DC 24 V		0...10 V, 2...10 V, 4...20 mA		p ¹⁾	
– Boiler plants			M3P..FY..		AC 24 V		0...10 V, 4...20 mA		p ¹⁾	
– Chiller plants			MVF461H..		AC/DC 24 V		0...10 V, 2...10 V, 0...20 mA, 4...20 mA		–	
– Domestic hot water			MXG461..		AC/DC 24 V		0...10 V, 2...10 V, 4...20 mA		p ¹⁾	
– Heating groups			MXG461B..		AC/DC 24 V		0...10 V, 2...10 V, 0...20 mA, 4...20 mA		–	
– Air handling units			MXG461S..		AC/DC 24 V		0...10 V, 2...10 V, 4...20 mA		–	
			MXG462S..		AC/DC 24 V		0...10 V, 2...10 V, 0...20 mA, 4...20 mA		–	
PN 16										
1...130 °C										
Data sheet			N4455		DN		k _{vs} [m³/h]		Δp _s [kPa] Δp _{max} [kPa]	
			MXF461.15-... ²⁾		15		0.6 / 1.5 / 3		300 300	
			MXF461.20-5.0		20		5		300 300	
			MXF461.25-8.0		25		8		300 300	
			MXF461.32-12		32		12		300 300	
			MXF461.40-20		40		20		300 300	
			MXF461.50-30		50		30		300 300	
			MXF461.65-50		65		50		300 300	
			1...120 °C							
			N4454							
			M3P80FY		80		80		300 300	
M3P100FY		100		130		200 200				
PN 16										
1...180 °C										
Data sheet			N4361		DN		k _{vs} [m³/h]		Δp _s [kPa] Δp _{max} [kPa]	
			MVF461H15-... ²⁾		15		0.6 / 1.5 / 3		1000 1000	
			MVF461H20-5		20		5		1000 1000	
			MVF461H25-8		25		8		1000 1000	
			MVF461H32-12		32		12		1000 1000	
			MVF461H40-20		40		20		1000 1000	
			MVF461H50-30		50		30		1000 1000	
			MVF461H50-30		50		30		1000 1000	
PN 16										
1...130 °C										
Data sheet			N4455		DN		G [Inch]		k _{vs} [m³/h] Δp _s [kPa] Δp _{max} [kPa]	
			MXG461.15-... ²⁾		15		G 1B		0.6 / 1.5 / 3 300 300	
			MXG461.20-5.0		20		G 1¼B		5 300 300	
			MXG461.25-8.0		25		G 1½B		8 300 300	
			MXG461.32-12		32		G 2B		12 300 300	
			MXG461.40-20		40		G 2½B		20 300 300	
			MXG461.50-30		50		G 2¾B		30 300 300	
PN 16										
-20...130 °C										
Data sheet			N4461		DN		G [Inch]		k _{vs} [m³/h] Δp _s [kPa] Δp _{max} [kPa]	
			MXG461B15-... ²⁾		15		G 1B		0.6 / 1.5 / 3 1000 1000	
			MXG461B20-5		20		G 1¼B		5 800 800	
			MXG461B25-8		25		G 1½B		8 700 700	
			MXG461B32-12		32		G 2B		12 600 600	
			MXG461B40-20		40		G 2½B		20 600 600	
			MXG461B50-30		50		G 2¾B		30 600 600	
PN 16										
1...130 °C										
Data sheet			N4465		DN		G [Inch]		k _{vs} [m³/h] Δp _s [kPa] Δp _{max} [kPa]	
			MXG461S15-1.5		15		G 1B		1.5 300 300	
			MXG461S20-5.0		20		G 1¼B		5 300 300	
			MXG461S2							

³⁾ Parts that are in contact with medium in stainless steel

Slipper valves

Typical applications	Actuators	Data sheet			5 Nm	10 Nm
– Boiler plants – Heating groups	SQK33.. SAL..	N4506 N4502				
	Operating voltage	Positioning signal	Positioning time [s]			
			SQK33	SAL		
	AC 230 V	3-position	125	120	SQK33.00	SAL31.00T10
		3-position	–	30	–	SAL31.03T10
	AC/DC 24 V	3-position	–	120	–	SAL81.00T10
		3-position	–	30	–	SAL81.03T10
		0...10 V, 4...20 mA	–	120	–	SAL61.00T10
0...10 V, 4...20 mA		–	30	–	SAL61.03T10	
Mounting set				ASK32	ASK31N	
PN 6	1...120 °C	DN	k _{vs} [m³/h]	Δp _{max} [kPa]	Δp _{max} [kPa]	
Data sheet	N4241					
 	VBF21.40	40	25	30	–	
	VBF21.50	50	40	30	–	
	VBF21.65	65	63	–	30	
	VBF21.80	80	100	–	30	
	VBF21.100	100	160	–	30	
	VBF21.125	125	550	–	30	
	VBF21.150	150	820	–	30	

Butterfly valves

Typical applications – Boiler plants – Chiller plants – Heating groups	Actuators	Data sheet			Rotation angle 90°							
	SAL.. Operating voltage AC 230 V AC/DC 24 V 3-position 3-position 3-position 3-position 0...10 V, 4...20 mA 0...10 V, 4...20 mA	N4502			10 Nm 		40 Nm 					
		Positioning signal			Positioning time [s]							
		3-position			120		SAL31.00T10		SAL31.00T40			
		3-position			125		–		–			
		3-position			30		SAL31.03T10		–			
		3-position			120		SAL81.00T10		SAL81.00T40			
		3-position			30		SAL81.03T10		–			
		0...10 V, 4...20 mA			120		SAL61.00T10		SAL61.00T40			
	0...10 V, 4...20 mA			30		SAL61.03T10		–				
Mounting set				ASK33N		ASK33N						
PN 6/10/16	-10...120 °C			DN	k _{vs} [m³/h]	Δp _s [kPa]		Δp _s [kPa]				
Data sheet	N4131											
	VKF41.40			40	50	500		–				
	VKF41.50			50	80	500		–				
	VKF41.65			65	200	500		–				
	VKF41.80			80	400	500		–				
	VKF41.100			100	760	500		–				
	VKF41.125			125	1000	300		–				
	VKF41.150			150	2100	250		400				
	VKF41.200			200	4000	125		300				

Typical applications – Boiler plants – Chiller plants – Cooling towers – Domestic hot water – Heating groups	Actuators	Data sheet		Rotation angle 90°								
	SAL.. SQL36.. Operating voltage AC 230 V AC/DC 24 V 3-position 3-position 3-position 3-position 3-position 0...10 V, 4...20 mA	N4502 N4505		20 Nm 	40 Nm 	40 Nm 		100 Nm 		400 Nm 	1200 Nm 	
		Positioning signal		time [s]								
		3-position		6 ¹⁾	–	–	–	–	SQL36E65	–	–	–
		3-position		12 ¹⁾	–	–	–	–	–	SQL36E110	–	–
		3-position		24 ¹⁾	–	–	–	–	–	–	SQL36E160	–
		3-position		25	–	–	SQL36E50F04	SQL36E50F05	–	–	–	–
		3-position		120	SAL31.00T20	SAL31.00T40	–	–	–	–	–	–
		3-position		120	SAL81.00T20	SAL81.00T40	–	–	–	–	–	–
	0...10 V, 4...20 mA		120	SAL61.00T20	SAL61.00T40	–	–	–	–	–	–	
PN 16	-10...120 °C		DN	k _{vs} [m³/h]	Δp _s [kPa]	Δp _s [kPa]	Δp _s [kPa]	Δp _s [kPa]	Δp _s [kPa]	Δp _s [kPa]	Δp _s [kPa]	
Data sheet	N4136											
	VKF46.40		40	50	1600	–	1600	–	–	–	–	
	VKF46.50		50	85	1600	–	1600	–	–	–	–	
	VKF46.65		65	215	1600	–	1600	–	–	–	–	
	VKF46.80		80	420	–	1600	–	1600	–	–	–	
	VKF46.100		100	800	–	1200	–	1600	–	–	–	
	VKF46.125		125	1010	–	800	–	1000	–	–	–	
	VKF46.150		150	2100	–	–	–	–	1600	–	–	
	VKF46.200		200	4000	–	–	–	–	1000	–	–	
	VKF46.250		250	6400	–	–	–	–	–	1000	–	
	VKF46.300		300	8500	–	–	–	–	–	1000	–	
	VKF46.350		350	11500	–	–	–	–	–	600	–	
	VKF46.400		400	14500	–	–	–	–	–	300	–	
	VKF46.450		450	20500	–	–	–	–	–	–	300	
	VKF46.500		500	21000	–	–	–	–	–	–	300	
	VKF46.600		600	29300	–	–	–	–	–	–	300	

¹⁾ With auxiliary module SEZ31.1 variable positioning time: SQL36E65: 30...180 s, SQL36E110: 60...360 s, SQL36E160: 120...720 s

Recommended maximum flow velocity:

VKF41...: < 4 m/s for water, see data sheet for details

VKF46...: 4.5 m/s for water, 60 m/s for gas

Changeover and open/close ball valves








Typical applications – Boiler plants – Chiller plants – Domestic hot water – Heating groups	Actuators	Data sheet			Spring return function [s]	2 Nm		7 Nm		10 Nm	
	GQD..9A GSD..9A GMA..9E GLB..9E	N4659 N4655 N4658 A6V10636203									
	Operating voltage	Positioning signal	Positioning time [s]								
			GQD/GSD	GMA		GLB					
	AC 230 V	2-position	30	90		–	15	GQD321.9A	GMA321.9E	–	
		2-position	30	–		–	–	GSD341.9A	–	–	
	AC 100...240 V	2/3-position	–	–		150	–	–	–	GLB341.9E	
	AC/DC 24 V	2-position	30	90		–	15	GQD121.9A	GMA121.9E	–	
		2-position	30	–		–	–	GSD141.9A	–	–	
		2/3-position	–	–		150	–	–	–	GLB141.9E	
PN 40	-10...120 °C	DN	G [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	
Data sheet	N4213										
	VAG60.15-9	15	G 1 B	9	1400	350	1400	350	1400	350	
	VAG60.20-17	20	G 1 ¼ B	17	1400	350	1400	350	1400	350	
	VAG60.25-22	25	G 1 ½ B	22	1400	350	1400	350	1400	350	
	VAG60.32-35	32	G 2 B	35	–	–	1000	350	1000	350	
	VAG60.40-68	40	G 2 ¼ B	68	–	–	800	350	800	350	
	VAG60.50-96	50	G 2 ¾ B	96	–	–	600	350	600	350	
PN 40	-10...120 °C	DN	G [Inch]	k _{vs} [m³/h]	Δp _{max} [kPa]	Δp _{max} [kPa]	Δp _{max} [kPa]				
Data sheet	N4213										
	VBG60.15-8T	15	G 1 B	8	350	350	350				
	VBG60.20-13T	20	G 1 ¼ B	13	350	350	350				
	VBG60.25-13T	25	G 1 ½ B	13	350	350	350				
	VBG60.32-25T	32	G 2 B	25	–	350	350				
	VBG60.40-49T	40	G 2 ¼ B	49	–	350	350				
	VBG60.50-73T	50	G 2 ¾ B	73	–	350	350				
PN 40	-10...120 °C	DN	Rp [Inch]	k _{vs} [m³/h]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	Δp _s [kPa]	Δp _{max} [kPa]	
Data sheet	N4213										
	VAI60.15-15	15	Rp ½	15	1400	350	1400	350	1400	350	
	VAI60.20-22	20	Rp ¾	22	1400	350	1400	350	1400	350	
	VAI60.25-22	25	Rp 1	22	1400	350	1400	350	1400	350	
	VAI60.32-35	32	Rp 1 ¼	35	–	–	1000	350	1000	350	
	VAI60.40-68	40	Rp 1 ½	68	–	–	800	350	800	350	
	VAI60.50-96	50	Rp 2	96	–	–	600	350	600	350	
PN 40	-10...120 °C	DN	Rp [Inch]	k _{vs} [m³/h]	Δp _{max} [kPa]	Δp _{max} [kPa]	Δp _{max} [kPa]				
Data sheet	N4213										
	VBI60.15-12T	15	Rp ½	12	350	350	350				
	VBI60.20-16T	20	Rp ¾	16	350	350	350				
	VBI60.25-16T	25	Rp 1	16	350	350	350				
	VBI60.32-25T	32	Rp 1 ¼	25	–	350	350				
	VBI60.40-49T	40	Rp 1 ½	49	–	350	350				
	VBI60.50-73T	50	Rp 2	73	–	350	350				
PN 40	-10...120 °C	DN	Rp [Inch]	k _{vs} [m³/h]	Δp _{max} [kPa]	Δp _{max} [kPa]	Δp _{max} [kPa]				
Data sheet	N4213										
	VBI60.15-5L	15	Rp ½	5	350	350	350				
	VBI60.20-9L	20	Rp ¾	9	350	350	350				
	VBI60.25-9L	25	Rp 1	9	350	350	350				
	VBI60.32-13L	32	Rp 1 ¼	13	–	350	350				
	VBI60.40-25L	40	Rp 1 ½	25	–	350	350				
	VBI60.50-37L	50	Rp 2	37	–	350	350				

Refrigerant valves									
Typical applications		Valve	Operating voltage		Positioning signal			Auxiliary functions	
– Chiller plants		M2FP03GX	AC 24 V		0...10 V, 4...20 mA, 0...20 Phs			–	
		MVL661..	AC/DC 24 V		0...10 V, 2...10 V, 0...20 mA, 4...20 mA			Minimum stroke setting	
		MVS661..N	AC/DC 24 V		0...10 V, 2...10 V, 0...20 mA, 4...20 mA			Minimum stroke setting	
		M3FB..LX..	AC 24 V		0...10 V, 4...20 mA, 0...20 Phs			–	
		M3FK..LX..	AC 24 V		0...10 V, 4...20 mA, 0...20 Phs			–	
PN 32	-40...100 °C						k_{vs} [m³/h]	Δp_{max} [kPa]	
Data sheet	N4731								
		M2FP03GX	Pilot valve				0.3	1800	
PS 45	-40...120 °C	DN	Connection	Inner Ø [Inch]			k_{vs} [m³/h]	k_{vs} reduced [m³/h]	Δp_{max} [kPa]
Data sheet	N4714								
	MVL661.15-0.4	15	Sleeve	5/8			0.4	0.25	2500
	MVL661.15-1.0	15	Sleeve	5/8			1	0.63	2500
	MVL661.20-2.5	20	Sleeve	7/8			2.5	1.6	2500
	MVL661.25-6.3	25	Sleeve	1 1/8			6.3	4	2500
	MVL661.32-10	32	Sleeve	1 3/8			10	6.3	1600
	MVL661.32-12	32	Sleeve	1 3/8			12	7.6	200
PN 63	-40...120 °C	DN	Connection	Inner Ø [mm]	Outer Ø [mm]		k_{vs} [m³/h]	k_{vs} reduced [m³/h]	Δp_{max} [kPa]
Data sheet	N4717								
	MVS661.25-016N	25	Weldable, solderable	22.4	33.7		0.16	0.1	2500
	MVS661.25-0.4N	25	Weldable, solderable	22.4	33.7		0.4	0.25	2500
	MVS661.25-1.0N	25	Weldable, solderable	22.4	33.7		1	0.63	2500
	MVS661.25-2.5N	25	Weldable, solderable	22.4	33.7		2.5	1.6	2500
	MVS661.25-6.3N	25	Weldable, solderable	22.4	33.7		6.3	4	2500
PN 32	-40...120 °C	DN	Connection	Inner Ø [Inch]			k_{vs} [m³/h]	Liquid Δp_{max} [kPa]	Gas Δp_{max} [kPa]
Data sheet	N4722								
	M3FK15LX06	15	Sleeve	5/8			0.6	200	800
	M3FK15LX15	15	Sleeve	5/8			1.5	200	800
	M3FK15LX	15	Sleeve	5/8			3	200	800
	M3FK20LX	20	Sleeve	7/8			5	200	800
	M3FK25LX	25	Sleeve	1 1/8			8	200	800
	M3FK32LX	32	Sleeve	1 3/8			12	200	800
	M3FK40LX	40	Sleeve	1 1/2			20	200	800
	M3FK50LX	50	Sleeve	2 1/8			30	200	800
PS 43	-40...120 °C	DN	Connection	Inner Ø [Inch]			k_{vs} [m³/h]	Δp_{max} [kPa]	
Data sheet	N4721								
	M3FB15LX06/A	15	Sleeve	5/8			0.6	2200	
	M3FB15LX15/A	15	Sleeve	5/8			1.5	2200	
	M3FB15LX/A	15	Sleeve	5/8			3	2200	
	M3FB20LX/A	20	Sleeve	7/8			5	1800	
	M3FB25LX/A	25	Sleeve	1 1/8			8	1200	
	M3FB32LX	32	Sleeve	1 3/8			12	800	

Symbols	
	3-port valve, control path with equal-percentage valve characteristic, bypass with linear valve characteristic.
	3-port valve, control path with equal-percentage valve characteristic, bypass with linear valve characteristic with 70% of the k_{vs} value. This compensates for the flow resistance of the heat exchanger, so that the total volumetric flow V_{100} remains as constant as possible.
	2-port valve, control path with equal-percentage valve characteristic.
	2-port valve or 6-port control ball valve in the respective control path with linear valve characteristic.
	3-port, control path and bypass with linear valve characteristic. Bypass with 70% of the k_{vs} value. This compensates for the flow resistance of the heat exchanger, so that the total flow amount V_{100} remains as constant as possible.
	3-port valve, control path and bypass with linear valve characteristic.
	3-port valve, control path and bypass with equal-percentage valve characteristic.

Valve sizing and actuator selection

Basic hydronic circuit

1	Determine the type of hydronic circuit	Throttling circuit	Injection circuit with 2-port valve	Diverting circuit	Injection circuit with 3-port valve	Mixing circuit	Mixing circuit with fixed premixing
	For valve sizing relevant variable flow path					Primary pump ✓  Primary pump ✗ 	Primary pump ✓  Primary pump ✗ 

HVAC plants and consumers

Heating

Surface/floor heating	–	■	–	outdated	–	–	■	■
Heating plant (primary)	–	■	■	outdated	■	■	■	■
Zone control, heating	–	■	–	outdated	–	–	–	–
Heating groups	–	■	–	–	■	■	■	■
Generation of heat energy	–	–	–	–	–	■	–	■
Heat exchanger water-water	■	uncommon	uncommon	uncommon	uncommon	–	–	–

Ventilation and air conditioning plants

Air handling unit (AHU)	■	■	■	outdated	■	■	–	–
Fan coil unit	■	–	■	outdated	–	–	–	–
Cooling coil	dehumidifying	–	dehumidifying	uncommon	–	–	–	–
Reheating coil	■	■	outdated	outdated	uncommon	uncommon	uncommon	uncommon
Preheating coil	–	■	–	outdated	uncommon	uncommon	uncommon	uncommon
VAV	■	–	■	outdated	–	–	–	–
Zone control	■	–	■	outdated	–	–	–	–

Chiller plants

Surface/floor cooling	–	■	–	outdated	–	–	–	–
Generation of cooling energy	–	–	–	–	–	■	–	■
Cooling towers	■	–	■	uncommon	–	–	–	–
Zone control, cooling	–	■	–	outdated	–	–	–	–

District heating and cooling

District heating, primary	■	uncommon	–	–	–	uncommon	–	uncommon
District heating, secondary	■	■	–	–	–	uncommon	–	uncommon
District cooling, primary	■	uncommon	–	–	–	uncommon	–	uncommon
District cooling, secondary	■	■	–	–	–	uncommon	–	uncommon

Domestic hot water (DHW)

DHW	–	■	–	–	–	■	–	–
-----	---	---	---	---	---	---	---	---

Header

Differential pressure header	pressurized		pressureless	
Volumetric flow	variable	constant	variable	

Determination of k_{VS} value

Δp_{VR} or Δp_{MV}		Δp_{VR}		Δp_{MV}					
2	typical range	10...200 kPa	10...200 kPa	10...50 kPa	2...5 kPa	2...5 kPa	5...15 kPa	2...5 kPa	5...15 kPa
	typical value	Use effective Δp_{VR} value		35 kPa	3 kPa	3 kPa	8 kPa	3 kPa	8 kPa
3	Determine Δp_{V100}	$\Delta p_{V100} \geq \frac{\Delta p_{VR}}{2}$		$\Delta p_{V100} \geq \Delta p_{MV}$					
4	Calculate V_{100}	Water without anti-freeze $V_{100} = \frac{Q_{100}}{1.163 \cdot \Delta T}$				Water with anti-freeze		$V_{100} = \frac{Q_{100} \cdot 3600}{c \cdot \rho \cdot \Delta T}$	
5	Determine k_{vs} value	$k_v = \frac{V_{100}}{\sqrt{\frac{\Delta p_{V100}}{100}}} \Rightarrow k_{vs} \geq 0.85 \cdot k_v \text{ value}$							
6	Check resulting Δp_{V100}	$\Delta p_{V100} = 100 \cdot \left(\frac{V_{100}}{k_{vs}} \right)^2$							

Selection of valve and actuator				
7	Select suitable valve series	a) Type of valve (2-port, 3-port, 3-port with bypass) b) Connections (flanged, threaded, soldered)	c) PN class d) Nominal size DN	e) Max. / min. medium temperature f) Medium
8	Check valve authority P_v (control stability)	$P_v = \frac{\Delta p_{v100}}{\Delta p_{VR}} \geq 0.25 \dots 0.8$ $P_v = \frac{\Delta p_{v100}}{\Delta p_{v100} + \Delta p_{MV}} \geq 0.25 \dots 0.8$		
9	Select actuator	a) Operating voltage	b) Positioning signal	c) Positioning time
10	Check working range	a) Differential pressure $\Delta p_{max} > \Delta p_{v0}$	b) Closing pressure $\Delta p_s > H_0$	d) Spring return function
11	Selection	Valve and suitable actuator		e) Auxiliary functions

Size and select combi valves

Determine volumetric flow V				
1	Determine Q_{100}	Q_{100}		
2	Determine ΔT	ΔT		
3	Calculate V	Water without anti-freeze	$V_{100} = \frac{Q_{100}}{1.163 \cdot \Delta T}$	Water with anti-freeze
				$V_{100} = \frac{Q_{100} \cdot 3600}{c \cdot \rho \cdot \Delta T}$
Select combi valve and actuator				
4	Select suitable combi valve	a) Type of valve (with / without P/T plugs) d) Connection (flanged, threaded)	b) PN class e) Nominal size DN	c) Max. / min. medium temperature f) Medium
5	Determine presetting	Determine presetting using the volumetric flow / dial table in data sheet of the respective combi valve		
6	Select actuator	a) Operating voltage	b) Positioning signal	c) Positioning time
7	Check working range	a) $\Delta p < \Delta p_{max}$ – maximum permissible differential pressure across the valve's control path, valid for the entire actuating range of the motorized valve b) $\Delta p > \Delta p_{min}$ – minimum differential pressure required across the valve's control path, so that the differential pressure regulator works reliably		
8	Select actuator	Combi valve and suitable actuator		

Definitionen

Abbr.	Term	Unit	Definition
Δp	Differential pressure	kPa	Pressure differential between plant sections.
Δp_{max}	Maximum differential pressure	kPa	Maximum permissible differential pressure across the valve's control path (when mixing), valid for the entire actuating range of the motorized valve.
Δp_{maxV}	Maximum differential pressure	kPa	Maximum permissible differential pressure across the valve's control path (when distributing), valid for the entire actuating range of the motorized valve.
Δp_{min}	Minimum differential pressure	kPa	Minimum differential pressure required, so that the differential pressure regulator works reliably with combi valves. Δp_{min} depends on presetting position, see data sheet for details.
Δp_{v0}		kPa	Maximum differential pressure across the valve's closed control path.
Δp_{v100}	Differential pressure at nominal flow rate	kPa	Differential pressure across the fully open valve and the valve's control path by a volumetric flow V_{100} .
Δp_s	Closing pressure	kPa	For 2-port valves, maximum permissible differential pressure at which the motorized valve will close securely against the pressure (close off pressure). Only valid for 2-port valves.
Δp_{MV}		kPa	Differential pressure across the variable flow path. Often Δp_{MV} is not known, in which case typical values can be used.
Δp_{VR}		kPa	Differential pressure between flow and return.
ΔT	Temperature spread	K	Temperature differential between flow and return.
DN	Nominal size		Characteristic for matching parts of the piping system.
H_0	Shutoff head	m	The head generated by a pump at closed valve, at a given speed and a given pump medium.
kPa	Unit of pressure	kPa	100 kPa = 1 bar = 10 mWC
mWS	Meter water column	m	
k_v	Nominal flow	m³/h	Amount of cold water (5...30 °C) passing through the valve at the respective stroke and at a differential pressure of 100 kPa (1 bar).
k_{vS}	Nominal flow rate	m³/h	Nominal flow rate of cold water (5...30 °C) through the fully open valve (H100) at a differential pressure of 100 kPa (1 bar).
	Spring return function		Shutoff in the event of a power failure.
PN	PN class		Characteristic relating to the combination of mechanical and dimensional properties of a component in the piping system.
PS	PS class		Maximum allowable pressure
Phs	Phase cut control signal	V	DC 0...20 V Phs
P_v	Valve authority		Ratio of differential pressure across fully open valve (H100) and differential pressure across valve and variable flow path. To ensure correct control, a minimum valve authority of 0.25 is required.
Q_{100}	Rated capacity	kW	Plant's design capacity.
V_{100}	Volumetric flow	m³/h	Volumetric flow with valve fully open (H_{100}).
V_{min}	Minimum volumetric flow	m³/h	Smallest presettable volumetric flow through the fully open combi valve (H_{100}).
ν	Kinematic viscosity	mm²/s	In the case of kinematic viscosities ν up to 10 mm²/s, no corrections are required. For the selection of actuating devices for kinematic viscosities ν above 10 mm²/s, please contact your local Siemens branch office.
c	Specific heat capacity	kJ/kgK	
ρ	Specific density	kg/m³	

People spend about 90 percent of their time indoors.

Improve the places where they spend their lives and
you improve their lives.

With our people and technology, our products and services,
our aim is to create perfect places.

For every stage of life.

When building technology creates perfect places –
that's Ingenuity for life.

[#CreatingPerfectPlaces](#)
siemens.com/perfect-places

Siemens Switzerland Ltd 2018
Building Technologies Division
International Headquarters
Theilerstrasse 1a
6300 Zug
Switzerland
Tel +41 41 724 24 24

Article no. 0-92205-en (Status 10/2018)

Subject to changes and errors. The information given in this document only
contains general descriptions and/or performance features which may not always
specifically reflect those described, or which may undergo modification in the
course of further development of the products. The requested performance features
are binding only when they are expressly agreed upon in the concluded contract.

© Siemens Switzerland Ltd, 2018